

バッテリー内蔵 Digital Signage

- 特殊キャスター付きの折りたたみ式デザインにより、一人でも柔軟に操作でき、時間と労力を節約できます。
- 高度なロック機構により、機械がしっかりと設置され、移動と設置が簡単かつ柔軟に行えます。
- IP65相当の防水・防塵性能
- 1500 高輝度 IPS スクリーンにより屋外での鮮明な視認性を確保
- バッテリーの使用量や充電時間を調整するのに便利な残量表示
- 14時間の長いバッテリー寿命



Panel parameter	Panel type	43"LCD Panel
	Display size (mm)	941.18×529.41mm(W*H)
	Display ratio	16: 9
	Backlight type	WLED
	resolution	1920*1080
	Display color	16.7M
	luminance	1500cd/m ²
	Contrast	1500: 1
	Viewing Angle	178°/178°
	Response time	5ms
Touch (optional)	type	Capacitive touch
	Touch mode	finger
	Effective touch recognition	≥5mm
	Touch accuracy	±1.5mm, Sensitive touch 90%
	Touch count	10
	Number of touches	unlimited
	First point response time	≤10 ms
	Continuous response time	≤5 ms
Android configuration parameters		RK3288 Default
Chip storage	CPU	Ruixin micro RK3288@1.8GHz A17 architecture
	GPU	Mail-T764
	Number of cores	quadrinucleus
	Operation and storage (RAM)	2GB(option 4GB)
	ROM)	16GB
	Storage collocation	2+16GB 4+32GB
	System version	Android 8.1
Network support	Ethernet	1 10M/100M adaptive Ethernet card
	WIFI	802.11b/g/n Wireless network card
	4G network card (optional)	4G (Telecom + Mobile + Unicom) selectable
	Bluetooth (optional)	BT4.0
port	storage	1 × TF (Micro-SD) MAX32G
	HDMI	1 × Input, 1 resolution output up to 3840*2160
	USB	1 × USB2.0
	Audio output	1 × 3.5mm audio interface
decode	Video format	wmv、avi、flv、rm、rmvb、mpeg、ts、mp4
	Picture format	Support BMP、JPEG、PNG
	Maximum decoding resolution	3840*2160
	Information release system	distribution
others	Overall power consumption	<200W
	Standby power consumption	<3W
	Operating ambient temperature	-10°C ~ 50°C
	Working ambient humidity	20% ~ 80%
	Screen surface	3mm thick explosion-proof tempered glass protection, anti-scratch and anti-collision
	Color	White
	Other interface	DC power supply plug (with our distribution special adapter), power switch, power display
	Class of protection	Class of protection

販売代理店



MEテック株式会社
〒141-0031
東京都品川区西五反田2-12-1
五反田Nビル8階
TEL 03-6887-8008
FAX 03-6887-8006